



Data Sheet Zhb

Mica - Barrel - Heaters Typ Zhb

- Heating of barrels on injection moulding machines and similar applications up to 350°C.

Technical Data

voltage	: 230 V or to customer
wattage	: to 3,5 W/cm ²
temp. max..	: 350°C
Ø min.	: 35 mm
height	: 20 mm - 800 mm
wall thickness	: ca. 4 mm
connection position	: to customer
connection	: power connection with plug socket or terminal box (with or without cable)



options

- with cut -outs and holes
- hole with bridge for thermocouple
- made of two halves or more segments
- power connection with plug socket or terminal box (with or without cable)
- reflector cover

**Other customer preferences are possible
Subject to modifications!**

05/02

Data Sheet Khb



Ceramic - Barrel - Heaters Typ Khb

- Heating of barrels on injection moulding machines and similar applications up to 450°C.

Technical Data

voltage	: 230 V or to customer
wattage	: to 7,5 W/cm ²
temp. max..	: 450°C
Ø min.	: 60 mm
height min.	: 21 mm
thickness	: ca. 12 mm
connection position	: to customer
thermal insulation	: 2 mm Isoplainsulation



options

- with drill holes and notches
- hole with bridge for thermocouple
- made of two halves or more segments
- power connection with plug socket or terminal box (with or without cable)
- reflector cover

**Other customer preferences are possible
Subject to modifications!**

05/02

Data Sheet KhbL



Ceramic - Heating - Cooling - Combinations Typ KhbL

- Heating and cooling of barrels on injection moulding machines and similar applications up to 450°C.

Technical Data

voltage	: 230 V or to customer
wattage	: to 7,5 W/cm ²
temp. max..	: 450°C
Ø min.	: 60 mm
height min.	: 21 mm
fan	: to customer
connection position	: to customer
connecting bracket	: to customer



options

- with cut-outs and holes
- power connection with plug socket or terminal box (with or without cable)

**Other customer preferences are possible
Subject to modifications!**

05/02